



Dimensions





TSD****S



TSD****A

TSD****F



TSD (Materials)

- 1 - Body: Nylon
- 2 - Cover: Nylon
- 3 - Seal: NBR
- 4 - Filter: Galvanised steel
- 5 - Anti-splash feature: Nylon
- 6 - Dipstick: Phosphated Steel

Quantity per pack
Number of Parts
TSD 25

| Size | A | Ø B | C | D | Ø E | Ø F | G |
|------------|----------|-----|------|----|-----|------|----|
| G16 | G 3/8" | 35 | 21 | 10 | 23 | 13,5 | 36 |
| G20 | G 1/2" | 39 | 21 | 11 | 27 | 17,5 | 36 |
| G26 | G 3/4" | 45 | 21 | 12 | 33 | 23,5 | 37 |
| G33 | G 1" | 51 | 24,5 | 13 | 39 | 29,5 | 44 |
| G42 | G 1 1/4" | 66 | 29,5 | 14 | 54 | 38 | 47 |
| G48 | G 1 1/2" | 66 | 29,5 | 14 | 54 | 38 | 47 |

N.B. Seals thickness 2 mm.
 Recommended tightening torque 10+15 Nm.

Ordering information

Filler cap

TSD
 Example: TSD **G20 R O A A F P01**

1 - Size

| | |
|------------|----------|
| G16 | G 3/8" |
| G20 | G 1/2" |
| G26 | G 3/4" |
| G33 | G 1" |
| G42 | G 1 1/4" |
| G48 | G 1 1/2" |

2 - Cover colour

| | |
|----------|--------|
| R | Red |
| Y | Yellow |

3 - Cover wording

| | |
|----------|---------|
| N | Neutral |
| O | Oil |
| G | Gasoil |

4 - Seal

| | |
|----------|-----|
| A | NBR |
|----------|-----|

5 - Filter element

| | |
|----------|--------------------------|
| A | Steel (excepté "Gasoil") |
| O | Without |

6 - Accessories

| | |
|----------|---------------------|
| S | Without |
| A | Standard dipstick |
| F | Anti-splash feature |

7 - Options

| | |
|------------|--------------------|
| P01 | MP Filtri standard |
|------------|--------------------|